


Evolution BLACK.power-16 BEB-2116

Das Netzkabel BEB-2116 wurde für eine stabile, verlustarme Stromversorgung in HiFi- und Studioanwendungen entwickelt. Drei feindrahtige OFC-Leiter bieten hohe Stromtragfähigkeit bei geringem Widerstand. LD-PE, Papierband und PVC-Isolierung schützen die Leiter zuverlässig. Eine doppelte Schirmung aus Aluminiumfolie und -geflecht blockiert Störeinflüsse. Ausgestattet mit Netzstecker und IEC-C15-Buchse, jeweils mit Carbonfaserhülse und vergoldeten Kontakten. Der Netzstecker ist in Varianten für unterschiedliche Länderstandards erhältlich.

Verpackungseinheit: 1 Stück (Set)

The BEB-2116 power cable is designed for stable, low-loss power delivery in HiFi and studio applications. Three fine-stranded OFC conductors offer high current capacity with low resistance. LD-PE, paper tape, and PVC insulation ensure reliable protection. Dual shielding with aluminum foil and braid blocks interference. The cable includes a power plug and an IEC C15 connector, each with a carbon fiber sleeve and gold-plated contacts. The plug is available in versions for different regional standards.

Packaging unit: 1 piece (set)



Technische Spezifikationen:

Leitermaterial	OFC
Leiterstruktur	3 × (128 × 0,20 mm OFC)
Querschnitt	3 × 4,1mm ² (11AWG)
Isolierung	LD-PE Ø 5,0 mm mit zusätzlicher PVC-Isolation
Schutzschicht	Papierband und Baumwollgarn
Schirmung	24#/11C/0,12 AL Geflecht + AL-Folie
Außenmantel	PVC Ø 15,0 mm, Baumwollgeflecht (schwarz/weiß)
Signalqualität	Zuverlässige Stromversorgung für HiFi-/AV-Geräte
Stecker	Netzstecker (ländertypisch) und IEC-C15, vergoldet, Metallhülse mit Carbonfaser
Verbindung	Netzstecker (M, länderspezifisch) auf IEC C15 Kaltgerätebuchse (F), 3-polig (L/N/PE)
Anwendung	Netzstromversorgung für HiFi-, AV- und Studio-Geräte

Technical Specifications:

Conductor Material	OFC
Conductor Structure	3 × (128 × 0.20 mm OFC)
Cross Section	3 × 4.1 mm ² (11 AWG)
Insulation	LD-PE Ø 5.0 mm with additional PVC insulation
Protective Layer	Paper tape and cotton yarn
Shielding	24#/11C/0.12 AL braid + AL foil
Outer Jacket	PVC Ø 15.0 mm, cotton braid (black/white)
Signal Quality	Reliable power supply for HiFi/AV devices
Connector	Power plug (region-specific) and IEC C15, gold-plated, metal sleeve with carbon fiber
Connection	Power plug (M, region-specific) to IEC C15 connector (F), 3-pin (L/N/PE)
Application	Power supply for HiFi, AV, and studio devices