

Blueberry KLANG.passend BB-008

Das Lautsprecherkabel BB-008 wurde für anspruchsvolle Stereoanwendungen entwickelt. Zwei symmetrisch verseilte Adern aus feindrahtigem OFC und Tinsel-Leitern sichern eine präzise, verlustarme Signalübertragung. LD-PE-Isolierung, Baumwoll-Füller und eine Luftkammer sorgen für Entkopplung und Flexibilität. Der PVC-Mantel mit Baumwollgeflecht schützt vor Belastungen. Vier vergoldete Stecker mit Metallhülsen sind als Gabel- oder Bananenstecker nutzbar und mit Richtungspfeilen markiert.

Verpackungseinheit: 2 Stück (Set)

The BB-008 speaker cable is designed for demanding stereo applications. Two symmetrically twisted conductors made of fine-stranded OFC and tinsel wires ensure precise, low-loss signal transmission. LD-PE insulation, cotton fillers, and an air chamber provide mechanical decoupling and flexibility. The PVC jacket with cotton braid protects against stress. Four gold-plated connectors with metal sleeves can be used as spade or banana plugs and are marked with directional arrows.

Packaging unit: 2 pieces (set)



Technische Spezifikationen:

Leitermaterial	OFC + Tinsel
Leiterstruktur	2 × (6 × (19 × Ø 0,12 mm OFC) + 6 × Ø 0,19 mm Tinsel)
Querschnitt	2 × 2,3 mm ² (13–14 AWG)
Isolierung	LD-PE Ø 2,6 mm
Schutzschicht	Papierband und Füller
Schirmung	LD-PE-Isolierung (Adern rot/weiß)
Außenmantel	PVC Ø 7,8 mm, Baumwollgeflecht (blau/schwarz)
Signalqualität	Hochauflösend, verlustarm
Stecker	Austauschbare Stecker, vergoldet, Hülse Metall, perlweiß oder silber lackiert
Verbindung	4 × Gabelstecker oder Federbanana (2 × rot, 2 × weiß), vergoldet
Anwendung	Stereo-Lautsprecherverbindung

Technical Specifications:

Conductor Material	OFC + Tinsel
Conductor Structure	2 × (6 × (19 × Ø 0.12 mm OFC) + 6 × Ø 0.19 mm Tinsel)
Cross Section	2 × 2.3 mm ² (13–14 AWG)
Insulation	LD-PE Ø 2.6 mm
Protective Layer	Paper tape and filler
Shielding	LD-PE insulation (red/white conductors)
Outer Jacket	PVC Ø 7.8 mm, cotton braid (blue/black)
Signal Quality	High-resolution, low loss
Connector	Replaceable connectors, gold-plated, metal sleeve, pearl white or silver coated
Connection	4 × spade connectors or spring bananas (2 × red, 2 × white), gold-plated
Application	Stereo speaker connection