

Blueberry SIGNAL. phonocinch BB-012

Das Phono-Signalkabel BB-012 wurde für analoge Plattenspieler mit separater Masseführung entwickelt. Zwei S-OCC-Leiter mit Skin- und FPE-Isolierung sichern verlustarme Signalübertragung. Eine doppelte Schirmung aus Aluminiumfolie und verzinnntem Kupfergeflecht schützt vor Störungen. Der flexible PVC-Mantel mit Baumwoll- und Nylongeflecht bietet Stabilität und Biegefestigkeit. Vergoldete RCA-Stecker und Y-Gabelschuh mit Metallgehäuse und Richtungspfeil sichern eine störungsfreie Verbindung.

Verpackungseinheit: 1 Stück (Set)

The BB-012 phono signal cable is specifically designed for analog turntables with separate grounding. Two S-OCC conductors with skin and FPE insulation ensure low-loss signal transmission. Dual shielding with aluminum foil and tinned copper braid reliably blocks interference. The flexible PVC jacket with cotton and nylon braid offers strength and bend resistance. Gold-plated RCA plugs and Y-spade terminal with metal housings and directional arrows ensure a noise-free connection.

Packaging unit: 1 piece (set)



Technische Spezifikationen:

Leitermaterial	S-OCC
Leiterstruktur	2 × (19 × Ø 0,12 mm 6N S-OCC)
Querschnitt	2 × 0,22 mm ² (24 AWG)
Isolierung	Skin + FPE Ø 1,75 mm
Schutzschicht	Geflecht aus Blankkupfer (24 × 7 × Ø 0,10 mm)
Schirmung	Innen: 55×0,10 BC-SP + AL-Folie Außen: AL-Folie + Geflecht
Außenmantel	PVC Ø 7,5 mm, Baumwollgeflecht (blau/schwarz)
Signalqualität	Extrem verlustarme Phono-Übertragung
Stecker	RCA, vergoldet, Hülse Metall, perlweiß oder silber lackiert
Verbindung	2 x RCA (L/R) auf 2 x RCA (L/R) + Masseleiter
Anwendung	Plattenspieler zu Vorverstärker

Technical Specifications:

Conductor Material	S-OCC
Conductor Structure	2 × (19 × Ø 0.12 mm 6N S-OCC)
Cross Section	2 × 0.22 mm ² (24 AWG)
Insulation	Skin + FPE Ø 1.75 mm
Protective Layer	Bare copper braid (24 × 7 × Ø 0.10
Shielding	Inside: 55 × 0.10 BC-SP + AL foil Outside: AL foil + braid
Outer Jacket	PVC Ø 7.5 mm, cotton braid (blue/black)
Signal Quality	Extremely low-loss phono transmission
Connector	RCA, gold-plated, metal sleeve, pearl white or silver coated
Connection	2 x RCA (L/R) to 2 x RCA (L/R) + ground wire
Application	Turntable to preamplifier